



EZ-Go Utility / Cargo Box Installation Instructions



KIT COMPONENTS

Item	Qty	Description
A	1	Cargo Box
B	2	Rear Cargo Box Supports
C	1	Left Seat Back/Cargo Box Support
D	1	Right Seat Back/Cargo Box Support
E	1	Hardware Kit



CAUTION:

Always disconnect the negative (-) cable from the battery before beginning. If your cart is equipped with a Tow/Run switch, always switch to the TOW position before working on your cart.

INSTALLATION INSTRUCTIONS:

1. If your cart is equipped with a top, you will need to remove the rear top supports first. It is best if you support the top temporarily using a broom stick, length of wood, or something long enough for this job. Save all of this hardware as it will be re-used.

NOTE: Use care when working under the top as your temporary support could slip and cause the top to fall.

2. Locate the two bolts on each side of the bag rack/seat cushion assembly and remove all 4 bolts. See figure 1.

3. Remove the 4 bolts securing the seat cushion to the bag rack assembly. The seat cushion will be re-used, but the bag rack will not. See figure 2. You're now ready to start assembling.

NOTE: Figure 2 shows the rear access panel removed, but it is not necessary to remove this for the Cargo Box kit installation.

4. Place the left seat back/cargo box support in place on the back of your original seat cushion. Make sure it is positioned as shown in figure 3. Secure it with two 1/4 X 1" long bolts and two 1/4" flat washers. DO NOT tighten at this time.

5. Now place the right seat back/cargo box support in place on the seat cushion and secure it as well. DO NOT tighten at this time.

6. Place the seat cushion and seat back/cargo box supports into place on the cart, as shown in figure 4. Secure it in place using the four 3/8 X 1" bolts and four 3/8" flat washers included in this kit.

7. Locate the two rear cargo box supports and position them in the rear bag well area as shown in figure 5 & 6. Use the two 5/16 X 1 1/2" bolts, four 5/16" flat washers and two 5/16" lock nuts to secure them in place. DO NOT tighten at this time.

8. Place the cargo box onto the back of the cart, with the tail gate to the rear.



Figure 1



Figure 2



Figure 3



Figure 4



Figure 5

9. Place the two 3/8 X 1" bolts with two 3/8" flat washers down through the two holes in the front of the cargo box. See figure 7. Adjust the box so that the two bolts drop through the holes in the seat back/cargo box supports. Add a 3/8" flat washer and lock nut to each, securing the front of the cargo box. DO NOT tighten at this time.




Figure 6

10. From the rear of the cargo box, secure the box support bracket to the two rear cargo box supports, using a 5/16 X 1" bolt, nut and two washers on each side. See figure 8.

11. You will want to stand back and look to make sure the cargo box is square on your cart. Once it is positioned where you want it, tighten all mounting bolts for the rear supports and cargo box.




Figure 7

12. The original top supports can now be installed. Use the four 5/16 X 2" bolts, eight 5/16" flat washers and four 5/16" lock nuts to secure the top supports to the holes provided in the cargo box supports, directly behind the seat back cushion. See figure 9.




Figure 8




Figure 9

**DO NOT TRANSPORT PASSENGERS
IN CARGO BOX!**